

□□ □□:

□□ □□ □□ □ □□ □□ □□ □□ □ □ □ □□, □□, □□ □□ □□□□ □□ □□ □ □□ □□ □□.  
□□ □□, □□, □□ □□ □□ □□ □□. □□ □□□□ □□ □ □ □□ □□ □ □ □□□ □□ □□ □□.



□□:

□□ □□□□.  
□□ □□ □□ □□ □□.  
□□ □□ □□ □ □ □□ □ □, □□ □□--□□ □□□□.  
□□ □□ □□ □□ □ □□ □ □ □□ □□-□□□ □□.

□□:

□□, □□, □□□, □□ □□



QINGDAO YUJING FANYU TRADING CO., LTD



☐☐☐ ☐☐:



Front of crates



Top of crates



Bottom of crates



Fumigated mark



Note on crates



Container



Empty container



Half loaded



Fully loaded



Closing container



Sealing



Delivery



Empty container



Half loaded



Fully loaded



Closing container



Sealing



Delivery

2mm/3mm/4mm/5mm/6mm □□ □□ □□□ □□



厚度公差	3mm/4mm/5mm/6mm 正负公差 ±0.15mm
认证	iso9001:2000, ce, tuv, 其他
性能	厚度 10% 以内，平整度 ±0.15mm，抗拉强度 ≥420MPa，伸长率 ≥18%，屈服强度 ≥320MPa，厚度公差 ±0.15mm，表面粗糙度 Ra 0.8
规格	1. 厚度 3mm 2. 厚度 4mm 3. 厚度 5mm 4. 厚度 6mm
表面处理	1. 表面平整度 ±0.15mm 2. 表面粗糙度 Ra 0.8 3. 表面光泽度 ≥60，表面平整度 ±0.15mm
包装	表面平整度 ±0.15mm，抗拉强度 ≥420MPa，伸长率 ≥18%，屈服强度 ≥320MPa，厚度公差 ±0.15mm，表面粗糙度 Ra 0.8
重量	2.0 mm, 3mm, 4mm, 5mm, 6mm
规格尺寸	1600 * 1830 * 2440 mm, 2250 mm, 2134 * 3300k
应用	医疗设备, 工业设备, 环保设备, 食品机械, 其他等.
其他	表面平整度 ±0.15mm, 厚度公差 ±0.15mm, 其他等.
交货期	1.2 周内交货，其他规格请咨询。 2. 其他规格请咨询。
服务	提供 15 天质保

联系我们:





☐☐ ☐ ☐☐☐☐:

Sales - sunny wang

Shouguang Yujing Business&Trading Co., Ltd.



[sunny@yujinggroup.cn](mailto:sunny@yujinggroup.cn)



276387631



cn1513198902



2753668305



WhatsApp

+86 18753639025



[sunny@yujinggroup.cn](mailto:sunny@yujinggroup.cn)

☐☐ ☐☐☐ (FAQ):

☐☐ ☐☐?

1. iso 9001:2000, tuv, 00 00 0.

2. 00 0 00 000 0 00 000 00 00.

3. 0000 0 0 0 000 0000 00 00 000 00 0 00 00 000 00 00 00.

4. 000 00 00 00.

5. 0000 0000 000.

6. 00 0 0 0000 00.

7. 000 000 00 0000 0 0 00 000 000 0 000 00 000 0000 000 000