

□□ □□:

□□ □□ □□ □ □□ □□ □□ □ □ □ □□, □□, □□ □□ □□□□ □□ □□ □ □□ □□ □□.
□□ □□, □□, □□ □□ □□ □□ □□. □□ □□□□ □□ □ □ □□ □□ □ □□□ □□ □□ □□.



□□:

□□ □□□□.
□□ □□ □□ □□ □□.
□□ □□ □□ □ □ □□ □ □, □□ □□--□□ □□□□.
□□ □□ □□ □□ □ □□ □ □ □□ □□-□□ □□.

□□:

□□, □□, □□□, □□ □□



QINGDAO YUJING FANYU TRADING CO., LTD



☐☐☐ ☐☐:



Front of crates



Top of crates



Bottom of crates



Fumigated mark



Note on crates



Container



Empty container



Half loaded



Fully loaded



Closing container



Sealing



Delivery



Empty container



Half loaded



Fully loaded



Closing container



Sealing



Delivery

2mm/3mm/4mm/5mm/6mm □□ □□ □□□ □□

厚度及公差	3mm/4mm/5mm/6mm 厚度公差 ±0.15mm
认证	iso9001:2000, ce, tuv, 其他
规格	厚度 10 种规格，厚度公差 ±0.15mm，厚度公差 ±0.15mm，厚度公差 ±0.15mm，厚度公差 ±0.15mm，厚度公差 ±0.15mm，厚度公差 ±0.15mm，厚度公差 ±0.15mm，厚度公差 ±0.15mm，厚度公差 ±0.15mm，厚度公差 ±0.15mm
应用	1. 铝板 2. 铝条 3. 铝管 4. 铝型材
表面处理	1. 阳极氧化 2. 电泳涂装 3. 氟碳漆
性能	铝板、铝条、铝管、铝型材、铝型材、e t c . 其他
厚度	2 mm, 3mm, 4mm, 5mm, 6mm
规格	1600 * 1830 * 2440 mm, 2250 mm, 2134 * 3300k
应用	铝板、铝条、铝管、铝型材、铝型材、铝型材 etc.
其他规格	铝板、铝条、铝管、铝型材、铝型材 etc.
厚度	1.2 种规格 2 . 种规格
其他	厚度公差 ±0.15mm

其他:





☐☐ ☐ ☐☐☐☐☐☐:

Sales - sunny wang

Shouguang Yujing Business&Trading Co., Ltd.



sunny@yujinggroup.cn



276387631



cn1513198902



2753668305



WhatsApp

+86 18753639025



sunny@yujinggroup.cn

faq:

☐☐☐☐☐?

1. iso 9001:2000, tuv, 00 00 00.

2. 00 0 00 000 0 00 000 00 00.

3. 0000 0 0 0 000 0000 00 00 000 00 0 00 00 0000 00 00 00.

4. 0000 00 00 00.

5. 0000 0000 000.

6. 00 0 0 0000 00.

7. 0000 0000 00 0000 0 0 00 0000 0000 0 0000 00 0000 0000 0000 0000 0000